



NWA50AX

802.11ax (WiFi 6) Dual-Radio PoE Access Point

The Zyxel NWA50AX is the true WiFi 6 access point that comes with the right-fit feature set for small businesses and SoHo users looking to upgrade to 11ax (WiFi 6) without an expensive price tag. Supporting both local GUI management and Nebula Cloud networking management, the simple setup of Zyxel NWA50AX allows you to quickly configure the AP with only a few clicks, making it super easy to set up guest and employee network on your own and start enjoying the ultra-fast WiFi 6 speeds in no time.

Supporting both 2.4Ghz and 5Ghz frequencies, the NWA50AX is aimed to empower you to enjoy all the best things WiFi 6 has to offer such as faster speeds even when congested or in high-density environments, expanded range in your wireless network, increased capacity for IoT deployments, and a lot more.

The NWA50AX with NebulaFlex offers the flexible manageability for you to freely choose between the local GUI management or onboarding to our super easy Nebula cloud management interface that you never need to worry about forgetting the IP address or lost account and password whatsoever.



Easy configuration allows you to set up guest and employee network in no time



Dual-radio (dual 2x2) 802.11ax AP provides maximum data rate of 1775 Mbps



NebulaFlex allows users to switch between standalone or intuitive Nebula cloud managed modes as needed



Advanced Cellular Coexistence minimizes interferences from 4G/5G cellular networks



The WPA3 Personal provides safer encryption



Smart Mesh automatically forms dynamic wireless links and mitigates complex, inconvenient cabling WiFi deployments

Benefits

Bringing next generation WiFi within reach

WiFi 6 made tremendous improvement by introducing new technologies, such as orthogonal frequency-division multiple access (OFDMA), and spatial re-use, which is also referred to as Basic Service Set (BSS) coloring. It aims to simultaneously satisfy all requirements from rapidly growing mobile users. Zyxel's NWA50AX is a true WiFi 6 access point which supports essential 11ax functions that delivers faster performance and increased capacity, making the user experience even better.

Apart from running at 25% faster speed, NWA50AX can also maximize WiFi efficiency by allowing simultaneous data transmission for multiple clients; thus, the air time contention is no longer an issue here.

NebulaFlex – simply manage it your way!


The NebulaFlex provides extended flexibility, allowing users to easily switch between standalone and our intuitive cloud-managed NCC (Nebula Control Center) mode any time according to your needs without additional cost while protecting wireless technology investments.

The Nebula cloud management platform provides centralized control and visibility over all Nebula networking devices. You simply need to register the device on NCC, and it will automatically join, auto provision and begin to give real-time information. The intuitive platform allows you to group your access points together, control centrally, gain access to diagnostics tools and additional features like captive portal all under a single platform.

4G/5G cellular network coexistence

With the exponential growth of mobile devices in the wireless network, users start to experience degraded performance, such as ping drops and high latency; users must reduce the use of their mobile devices in order to maintain a smooth, working wireless service. Thus, to enable 4G/5G cellular network coexistence and minimize interference from 4G/5G antennas or signal boosters, the NWA50AX has built-in 4G/5G interference filters. As a result, the visible or invisible 4G/5G indoor antennas in the environment is no longer an issue when installing APs.

Specifications

Model	NWA50AX	
Product name	802.11ax (WiFi 6) Dual-Radio PoE Access Point	
		
Wireless		
Standard	IEEE 802.11 ax/ac/n/g/b/a	
MIMO	MU-MIMO	
Wireless speed	2.4 GHz	575 Mbps
	5 GHz	1200 Mbps
Frequency band	2.4 GHz (IEEE 802.11 b/g/n)	<ul style="list-style-type: none"> • USA (FCC): 2.412 to 2.462 GHz • Europe (ETSI): 2.412 to 2.472 GHz
	5 GHz (IEEE 802.11 a/n/ac)	<ul style="list-style-type: none"> • USA (FCC): 5.15 to 5.35 GHz; 5.470 to 5.850 GHz • European (ETSI): 5.15 to 5.35 GHz; 5.470 to 5.725 GHz
Bandwidth	20-, 40-, 80-MHz	
Conducted typical transmit output power	US (2.4 GHz/5 GHz)	23/26 dBm
	EU (2.4 GHz/5 GHz)	20/25 dBm
RF Design		
Antenna type	2x2 + 2x2 MIMO embedded antenna	
Antenna gain	2.4 GHz	3 dBi
	5 GHz	4 dBi
Minimum receive sensitivity	Min. Rx sensitivity up to -99 dBm	
WLAN Feature		
Band steering	Yes	
WDS/Mesh	Yes	
Fast roaming	Yes	
DCS	Yes	
Load balancing	No	
Security		
Encryption	WPA/WPA2/WPA3 Personal	
Authentication	No	
Access management	MAC filtering/ Rogue AP detection	
Networking		
IPv6	Yes	
VLANs	Yes	
WMM	Yes	
U-APSD	Yes	

Model		NWA50AX
Management		
Operating mode	Cloud managed / standalone	
ZON Utility	<ul style="list-style-type: none"> • Discovery of Zyxel switches, APs and gateways • Centralized and batch configurations <ul style="list-style-type: none"> ▪ IP configuration ▪ IP renew ▪ Device reboot ▪ Device locating ▪ Web GUI access ▪ Firmware upgrade ▪ Password configuration 	
Zyxel Wireless Optimizer	WiFi AP planning	
Web UI/CLI	Yes	
SNMP	NO	
Physical Specifications		
Item	Dimensions (WxDxH)(mm/in.)	140 x 140 x 37.5 / 5.51 x 5.51 x 1.48
	Weight (g/lb.)	290 / 0.64
Packing	Dimensions (WxDxH)(mm/in.)	240 x 155 x 60 / 9.45 x 6.10 x 2.36
	Weight (g/lb.)	600 / 1.32
Included accessories	<ul style="list-style-type: none"> • Power adapter • Mount plate • Mounting screws 	
MTBF (hr)	1,010,980	
Physical Interfaces		
Ethernet port	1 x 10/100/1000M LAN	
Power	<ul style="list-style-type: none"> • Input: AC 100 - 240V - 50/60 Hz 0.3A; Output: DC +12V 1.5A • PoE (802.3at): power draw 16 W 	
Environmental Specifications		
Operating	Temperature	0°C to 50°C/32°F to 122°F
	Humidity	10% to 90% (non-condensing)
Storage	Temperature	-40°C to 70°C/-40°F to 158°F
	Humidity	10% to 90% (non-condensing)
Certifications		
Radio	FCC Part 15C, FCC Part 15E; ETSI EN 300 328, EN 301 893; LP0002, EN 60601-1-2	
EMC	FCC Part 15B, EN 301 489-1; EN 301 489-17, EN55022, EN55024, EN61000-3-2/-3, BSMI CNS13438	
Safety	EN 60950-1, IEC 60950-1; BSMI CNS14336-1	

For more product information, visit us on the web at www.zyxel.com

Copyright © 2021 Zyxel and/or its affiliates. All rights reserved.
All specifications are subject to change without notice.



24/05/21